



Machinery - Combination Saws - 250 mm Combination Saw

DW743N



DW743N Features

- The classic TGS flip-over bevelling saw
- Rapid tool free transformation from a saw bench to a mitre saw provides flexibility in a range of site and workshop applications
- Handle mechanism allows the guard to retract automatically in mitre mode allowing safe and easy use
- New high output heavy duty high torque induction motor provides years of maintenance free use, suitable for workshop applications where low noise characteristics are desirable
- Three way extractor connection facility for efficient dust extraction
- Integrated carry handles provide greater portability
- Updated design for maximum cutting capacity across the range of mitre and bevel angles

DW743N Specifications

Power Input	2000 Watts
Power Output	1550 Watts
Blade Speed	2850 rpm
Blade Diameter	250 mm
Blade Bore	30 mm
Bevel Capacity	45 °
Mitre Capacity [right/left]	45 / 45 °
Cutting Capacity at 90°/90° (W x H)	140 x 68 mm
Cutting Capacity at 90°/90° (W x H)	180 x 20 mm
Cutting Capacity at 45°/90° (W x H)	95 x 70 mm
Cutting Capacity at 45°/90° (W x H)	120 x 46 mm
Cutting Capacity at 90°/45° (W x H)	70 x 95 mm
Cutting Capacity at 90°/45° (W x H)	150 x 20 mm
Max. Cutting Capacity at 45°/45°	- mm
Max. Cutting Capacity [Sawbench position 90°/90°]	0 - 70 mm
Max. Cutting Capacity [Sawbench position 90°/45°]	0 - 32 mm
Weight	37 kg
Depth	670 mm
Length	700 mm
Height	750 mm

DW743N Standard

- 30 tooth saw blade
- Parallel fence
- Push stick
- 4 detachable legs
- Saw blade guard
- Assembly tool