



## Installation

Unroll Visqueen Flame Retardant Polythene Protection and cut to fit the area that needs protecting. For large covered areas it may be necessary to lap adjacent film sheets and a taped joint is recommended to ensure continuity of protection. When taping, allow an overlap of at least 50mm and secure the joint using Visqueen FR Single Sided Tape. Prior to taping ensure that the lap area is clean and free from dust and any moisture.

**For full installation instructions, please see product Technical Datasheet**



## System components

- Visqueen FR Single Sided Tape, 50mm x 50m

## Product description

### Visqueen Flame Retardant Polythene Protection

is manufactured using virgin polymers with specific additives to ensure the product is flame retardant to LPS1207 - Loss Prevention Standard cert no. 1792a/02.

The sheeting is supplied as centre folded rolls on a supporting core. Standard roll sizes are:

- 4m x 25m x 250 micron (Orange)
- 4m x 50m x 65 micron (White)

## Usage

Visqueen Flame Retardant Polythene Protection can be used for screening off individual areas, draping and for a variety of surfaces. The product can be easily cut and re-sized for pallet hood / cover protection.

Flame retardant sheeting can be also used in various other applications whilst buildings undergo refurbishment work or in new build construction projects whilst also providing protection from dust and the risks of electrical hazards.

## Features and benefits

- LPS1207 cert.no 1792a/01 - 3rd party flame retardant certification for Temporary Protection materials
- Large roll format - Ideal for draping, screening, covering or hanging. Quick and easy installation.
- Flame retardant - helps reduce the risk of losses from fires on construction sites
- 0.25mm (1000 gauge) thick - Approved for asbestos removal or wrapping film

