

Product Description

High performance 30micron aluminium foil tape coated with water based acrylic adhesive, lined with a strong release paper.

Applications

HVAC sealing of joints, jointing of aluminium insulation boards, flexible air duct seams and connections. General purpose holding, patching, sealing and masking applications indoors & out.

Features & Benefits

Excellent in medium to low temperatures and humidity applications

Soft foil conforms to irregular surfaces

Certified to BS476 part 6 & 7 Class "O" standard – **Superseded by BS EN 13051-1 Class B**

Technical Performance

Description	Units	Value	Test method
Foil thickness	mm	0.030	ASTM D3652
Total thickness	mm	0.065	ASTM D3652
Adhesion to steel	N/25mm	12	ASTM D3330
Tack rolling ball	cm	5	ASTM D3121
Tensile strength	N/25mm	45	ASTM D3759
elongation	%	3	ASTM D3759
Service temp	°c	-30 to +120	-
Application temp	°c	+10 to +40	-

Declaration of Conformity Information

Class "O" approval - Tested in accordance with BS476: Part6:1989 +A1:2009 and BS476: Part7:1997 **Superseded by
BS EN 13051-1 Class B Tested in accordance with ISO 11925-2:2020 & BS EN 13823:2020**

REACH SVHC Status

NO SHVC present according to candidates list of the **UK 25/06/20 & EU 27/06/24**

RoHS Compliance Status Yes

Storage Details

Store at the moderate temperature and humidity environment.