

# Heat Gun

## HG6531C

2 000 W • 200 – 550 l/min • 50 – 650 °C

**Heat gun with electronic control and variable heat and airflow settings**

An electronic 2 000 W heat gun for demanding use in a wide range of applications, including paint stripping. The heat gun has an adjustable heat range of between 80° and 650°C and pre-set heat and air flow settings. It is also equipped with four different nozzles.



### Technical specifications

Continuous Input Power	2000 W
Maximum Flow Rate	200 - 550 L/min
Temperature Range	50 - 650 °C
Max. Temperature	650 °C
Variable Temperature	✓
Thermal Safety Switch	✓
Weight Without Cable	0,71 kg
Product Dimensions (L x W x H):	257 x 85 x 206 mm
IEC Protection Class	II
Power Supply Cord	2,0 m

### User benefits

- Variable temperature control
- The rubber coating on the handle ensures a firm working grip
- Variable speed control dial enables user to match the speed to the application for greater versatility
- With overheat protection

Link to product - [www.makita.uk.com](http://www.makita.uk.com)



# Related products

Optional AC

PR00000029

Wide Slot Nozzle, 50 mm




PR00000030

Reflection Nozzle, 40 mm



PR00000031

Reduction Nozzle, 20 mm




PR00000036

Welding Rods, ABS, 5 x 230 mm, 10



PR00000037

Welding Rod, HDPE, 10 pcs



PR00000038

Welding Rod, PP, 10 pcs



Other

User manual

Parts drawing